

SYSTEM AND METHOD FOR SENDING OUT-OF-BAND SERVICE
INFORMATION TO A HOST DEVICE

Field of the Invention

5 This invention relates to a system for sending out-of-band (OOB) service information and, more particularly, to a system for sending out-of-band service information from a data module, such as a point of deployment (POD) module, to a host system, such as a set-top box.

Background of the Invention

10 Digital video and audio consumer electronics/devices are used by consumers to receive and conduct numerous services and transactions, for example, to receive video, audio and data streams from a (cable television) service provider, such as Emergency Alerting, Interactive Program Guides, Impulse Pay-Per-View (IPPV), Video On Demand (VOD), General Messaging, and Interactive Services.

15 In particular, one such a host device is a set-top box. A data module, such as a point of deployment (POD) module is a removable card inserted into a host device. As is well known the art, a POD module provides several functions including security that is physically separate from a set-top box's navigation function and parsing out-

of-band cable signals. For additional details on POD
modules, see SOCIETY OF CABLE TELECOMMUNICATIONS ENGINEERS,
INC. (SCTE) Document: SCTE DVS 131 Rev. 7, entitled "Draft
Point-of-Deployment (POD) Module Interface Proposal" dated
5 December 3, 1998, (hereinafter known as "DVS131r7").

Consumers rely on such devices to communicate, access
programs and services or engage in commercial transactions.

As noted, a host device, such as a set-top-box (STB)
or a cable-ready DTV receiver is used in conjunction with a
10 point of deployment (POD) module to receive desired
services. For example, the STB receives programs and
services in the form of elementary streams from a service
provider. The elementary streams are sent inside in-band
(IB) transport streams to the STB and forwarded to the POD
15 module so that scrambled programs can be descrambled by POD
module. Thereafter, the transport streams are sent back to
the host through the POD-to-host transport stream (TS)
channel for demultiplexing and decoding.

The STB must receive service information (or
20 electronic program guide) data from the service provider in
order to navigate through the received services and
programs. The service information on free services (e.g.
must-carry broadcast programs) is carried in-band as part
of transport streams. The service information on paid

services (e.g. pay-per-view services) is carried out-of-band (OOB). The OOB service information is transmitted from the service provider to the POD module inside the OOB data. The OOB service information is retrieved from the OOB data by the POD module and delivered to the host.

The existing method for delivering OOB service information from a POD module to a host device is through a data channel, a so-called extended channel, between the POD module and the host device. The extended channel is separate from the POD-to-host transport stream (TS) channel for delivering transport streams.

This method has several shortcomings including that the host must process system information from different sources - the POD-to-host TS channel and the extended channel, and more importantly, that the bandwidth of the extended channel and the overhead associated with the way the extended channel works limits the throughput of the service information crossing the extended channel.

Thus, there is a clear and present need for an effective means to provide OOB service information from the POD module to the host in a less restrictive manner.

Summary of the Invention

It is an object of the present invention to provide OOB service information to a host device in the transport streams transmitted in a data module, such as a point of deployment (POD) module, to host device, such as a set-top box, via the transport stream channel.

It is a further object of the present invention to allow a host device to accommodate IB and OOB service information in a uniform way, wherein limited or no change is necessary for an existing host device to receive OOB service information carried with transport streams and using the IB POD-to-host TS channel that has increased bandwidth for carrying extra data than the extended channel.

The problems associated with delivering OOB service information from a data module to a host device are reduced or overcome by an arrangement in accordance with the principles of the invention in which the OOB service information delivered in the transport streams transmitted in a data module, such as a point of deployment (POD) module, to host device, such as a set-top box, via the transport stream channel.

Brief Description of the Drawing

The invention will be more readily understood after reading the following detailed description taken in conjunction with the accompanying drawing, in which:

5 FIG. 1 illustrates an exemplary system in accordance with the principles of the present invention; and

10 FIG. 2 is a flowchart depicting the process for delivering OOB service information from a data module to a host device using the transport stream channel in the system of FIG 1.

Detailed Description

15 FIG. 1 is an exemplary system according to the principles of the present invention in which OOB service information delivered to a host device in the transport streams (TS) transmitted in a data module-to-host TS channel. It will be recognized that FIG. 1 is simplified for explanation purposes and that the full system
20 environment for the invention will comprise, for example, a cable, fiber or satellite service provider network or provisions for network reliability through redundancy, all of which need not be shown here. The system illustratively includes a host device 10, such as a set-top box and a data

module 12, such as a point of deployment (POD) module,
which communicate with each other through a communication
medium, for example, wireless communication,
electromagnetic card interface, optical communication, and
5 the like.

Data module 12, includes an out of band (OOB) data
parser 14, descambler 16, buffer 28, and a processor 18.

The majority of logic, control, supervisory,
translation functions required for the operation of data
10 module 12 is performed by processor 18 which also includes
programs for the operations functionally described in FIG.

2. As described in detail below, execution of these
program implements the functionality necessary to deliver
OOB service information via the transport streams in the
15 data module-to-host TS channel. Processor 18 can be any of
a number of commercially available processors.

Although data module 12 is described as a POD, this
arrangement is merely for convenience and it is to be
understood that data modules are not limited to PODs, per
20 se. As used herein, the term "data module" refers to any
type of (1) point of deployment module, (2) wireless,
cellular or radio data interface appliance, (3) smartcard
(4) personal computer, and (5) internet interface
appliance, which facilitates the transfer of data, access

remote services or engage in transactions.

Host device 10 communicates with data module 12 through the communication medium. Host device 10 includes a receiver 20, to receive elementary streams from a server provider, a demultiplexer 22, decoder 24 and a processor 26.

Similar to the data module, the majority of logic, control, supervisory, translation functions required for the operation of the authentication center are performed by processor 26 which also includes programs for the operations functionally described in FIG. 2. As described in detail below, execution of these programs implements the functionality necessary to deliver OOB service information via the transport streams in the data module-to-host TS channel. Processor 26 can be any of a number of commercially available processors.

The principles of the present invention are particularly useful for the OOB service information delivery from a POD module to a Host in a service provider communications network, such as a cable television network. However, it is to be understood that the steps described below in FIG. 2 are equally applicable to other devices indicated above.

For one example, to better understand how the OOB TS packets are inserted, assume the data throughput of the original TS packets is 38 Mbps (Mega bits per second), roughly 25266 TS packets per second, and the maximum data throughput for the IB channel, 50 Mbps, is roughly 33245 TS packets per second. (A TS packet has $188 \times 8 = 1504$ bits.) This means that we have room or gap for inserting roughly 8000 TS packets per second into the IB channel. Let us assume that we have 5000 packets per second to be inserted. To achieve this, we have, for example, a scheduler that makes sure that roughly for every $25299/5000 = 5$ original TS packets sent, one OOB TS packet is sent.

Thereafter, in step 210, the host device processes the OOB TS packets to receive OOB service information

The functions of the various elements shown in the FIGs. 1-2, may be provided through the use of dedicated hardware as well as hardware capable of executing software in association with appropriate software. When provided by a processor, the functions may be provided by a single dedicated processor, by a single shared processor, or by a plurality of individual processors, some of which may be shared. Moreover, explicit use of the term "processor" or "controller" should not be construed to refer exclusively to hardware capable of executing software, and may

0974563-132100
implicitly include, without limitation, digital signal
processor (DSP) hardware, read-only memory (ROM) for
storing software, random access memory (RAM), and
non-volatile storage. Other hardware, conventional and/or
5 custom, may also be included.

The following merely illustrates the principles of the
invention. It will thus be appreciated that those skilled
in the art will be able to devise various arrangements
which, although not explicitly described or shown herein,
10 embody the principles of the invention and are included
within its spirit and scope. Furthermore, all examples and
conditional language recited herein are principally
intended expressly to be only for pedagogical purposes to
aid the reader in understanding the principles of the
15 invention and the concepts contributed by the inventor(s)
to furthering the art, and are to be construed as being
without limitation to such specifically recited examples
and conditions. Moreover, all statements herein reciting
principles, aspects, and embodiments of the invention, as
20 well as specific examples thereof, are intended to
encompass both structural and functional equivalents
thereof. Additionally, it is intended that such
equivalents include both currently known equivalents as
well as equivalents developed in the future, i.e., any

